



Elegant Design
 High Performance
 Flexible Ergonomics

The POS-510 EyePOS GT II has the character of a stylish sports car. Just like the POS-500 EyePOS II, it is a POS system with the glass metal stand engineered by 4POS that shines without and convinces within. New with increased graphics/processor performance and USB3.0. With this series, 4POS has developed a compact all-in-one POS solution absolutely matchless in design. The POS terminal can be used freestanding on the counter, fixed at the checkout, mounted on the wall – it really couldn't be more flexible.



Touch System POS-500 EyePOS II POS-510 EyePOS GT II



1. Bezel-free touch



2. Standard configuration with unique EyeSTAND POS in metal glass construction




3. Optional 8.4" stand alone customer display



4. Optional VFD stand alone customer display



5. Optional 8.4" rear mount customer display



6. Rich I/O connector ports
 - 5 x USB 2.0
 - up to 2 x USB 3.0



POS-500 EyePOS II POS-510 EyePOS GT II



Model Name	POS-500 EyePOS II	POS-510 EyePOS GT II
Housing		
Material	Die-cast Magnesium-Aluminium	
Mount	VESA 100	
Mainboard		
	D36	D66
CPU	Intel Celeron J1900 2.0GHz (fanless)	Intel Celeron G1820TE 2.2GHz / Intel Core i5-4590T 2.0/3.0GHz
Chipset / GPU	Intel HD Graphics	Intel Q87 PCH (AMT/RAID enabled) / Intel HD Graphics
System Memory	1 x DDR3L-1600 SO-DIMM up to 8GB	
Display / Touch		
Display Size	15" TFT LCD with LED backlight	
Brightness	250 cd/m ²	
Maximum Resolution	1024 x 768	
Touch Screen Type	Resistive or Capacitive	
Tilt Angle (Degree)	30° Low Stand / 70° High Stand	
Storage		
Primary Device Bay	1 x 2.5 SATA (HDD or SSD)	
Flash Memory	1 x mSATA SSD	
External I/O Ports		
USB	6 x USB (5 x USB 2.0 + 1 x USB 3.0)	7 x USB (5 x USB 2.0 + 2 x USB 3.0)
Parallel Port	N/A	
Serial/COM	3 x COM ports with RJ-45 (5V/12 power selectable by BIOS) + 1 x COM with DB9	3 x COM ports with RJ-45 (5V/12 power selectable by BIOS) + 1 x COM with DB9
LAN	1 x RJ-45 (10/100/1000 Mbit)	
VGA out	1 x D-Sub (15 pin) with Power over VGA (activated via BIOS)	
Cash Drawer	1 x RJ-11 with 12V or 19V	
Speaker	2 x 2W	
Audio	1 x Line out	
Control/Indicator		
Power Button	1 with Power LED	
Power Supply	External, DC 19V (65W)	External, DC 19V (120W)
Environment		
EMC & Safety	FCC, Class A, CE, LVD	
Operating Temperature	5° C ~ 35° C	
IP	IP65 sealed front panel with touch screen	
Options		
Second Display	8.4" TFT LCD / VFD Display (2 x 20, 5mm character)	
WLAN	802.11 a/b/g mini PCI-E Wireless LAN Card	
Magnetic Card Reader	3 tracks MSR (via USB)	
Dimension (W x D x H)		
Panel PC only	361 x 60 x 278 mm	
with EyeSTAND POS Low	361 x 275 x 173 mm	
with EyeSTAND POS High	361 x 228 x 283 mm	
Weight		
	4.8 kg	5.1 kg
Colour		
	Black or Glossy White	
OS Support		
	Windows 7, 8.x, 10 / Linux	

V1601

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

