

High Performance
Ultra Sleek
Wide Aspect Ratio

The POS-560 WidePOS GT II convinces due to the installed components. Just like the POS-550 WidePOS II, it is a POS system with the glass metal stand engineered by 4POS that shines without and convinces within; new with increased graphics/processor performance and USB3.0. Three different screen sizes in 16:9 format (naturally dust- and water-protected) allow for unlimited possibilities for use. While this touch system is sleek, stylish and elegant in appearance, it is also powerful, extremely rugged and easy to service.



Touch System POS-550 WidePOS II POS-560 WidePOS GT II



1. Metal housing
IP65 dust & water
proof display front



2. Rich I/O ports provide
excellent peripheral con-
nectivity




3. Optional accessories
MCR, Fingerprintreader



4. Ultra slim, 48 mm thick-
ness



5. Bezelfree 5-Wire Resis-
tive and Projected
Capacitive Multi-Touch



6. Full range of display sizes
15.6", 18.5"
and 21.5"



POS-550 WidePOS II POS-560 WidePOS GT II



Model Name	POS-550 WidePOS II		POS-560 WidePOS GT II	
Housing				
Material	Die-cast Aluminium			
Mount	VESA 75			
Mainboard				
	D36		D66	
CPU	Intel Celeron J1900 2.0GHz (fanless)		Intel Celeron G1820TE 2.2GHz, Intel Core i5-4590T 2.0/3.0GHz	
Chipset / GPU	Intel HD Graphics		Intel Q87 PCH (AMT/RAID enabled), Intel HD Graphics	
System Memory	1 x DDR3L-1600 SO-DIMM up to 8GB			
LCD Touch Panel				
LCD Size	15.6" TFT LCD with LED backlight	18.5" TFT LCD with LED backlight	21.5" TFT LCD with LED backlight	
Brightness	250 cd/m ²			
Maximal Resolution	1366 x 768		1920 x 1080	
Touch Screen Type	Bezelfree resistive or projected capacitive touch		Capacitive touch	
Storage Device				
Primary Device Bay	1 x 2.5 SATA (HDD or SSD)			
External I/O Ports				
USB	5 x USB (4 x USB 2.0 + 1 x USB 3.0)		6 x USB (4 x USB 2.0 + 2 x USB 3.0)	
Serial/COM	4 x COM ports RJ-45 COM1/COM2/COM3 (0V/5V/12V power selectable by BIOS)/COM4 (no power option)			
Parallel Port	N/A			
LAN	2 x RJ-45 (10/100/1000 Mbit)			
VGA	1 x D-Sub (15 pin) with Power over VGA (activated via BIOS) + DVI-D			
Cash Drawer	1 x RJ11			
Speaker	2 x 2W			
Audio	1 x MIC in + 1 x Line out			
Control / Power				
Power Button	1 (bottom)			
Power Supply	External, DC 19V (65W)		External, DC 19V (120W)	
Environment				
EMC & Safety	FCC Class A, CE, LVD			
Operating Temperature	5° C ~ 35° C			
Operating Humidity	20% ~ 85% RH non condensing			
IP	IP65 (front panel)			
Options				
Web cam (built in)	2M web cam			
Second Display	8.4" TFT LCD / VFD Display (2 x 20, 5mm character)			
WLAN	802.11 a/b/g mini PCI-E Wireless LAN Card			
Magnetic Card Reader	3 tracks MSR (via USB)			
Fingerprintreader	1			
Dimension (WxDxH)				
Panel PC only	396 x 48 x 245 mm	464 x 48 x 284 mm	536 x 48 x 328 mm	
Weight				
	4.5 kg	6.8 kg	7.4 kg	
Colour				
	Black or Glossy white			
OS Support				
	Windows 7, 8.x, 10 / Linux			

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

V1601

