## High speed, LCD control POS printing

Retail class leader



### LCD display

The industry's first POS printer with LCD display for easy configuration and operation. Many set up options and coloured status or error messages.

#### In a hurry?

With 300mm/sec. print speed the CT-S801II is the fastest POS printer in the market.

#### **Tool-free maintenance**

Paper jam? No problem for the CT-S801II. One hand grip and the cutter is released automatically. No tool is needed. Even if the long-life cutter ever needs to be exchanged. Thanks to it's snap-In design this only takes 30 seconds.

## CT-S801II

POS, Receipt printer (thermal 3 inch / 80mm)

### **Applications**

- Hospitality
- Kiosk
- Kitchen
- Retail



Fast, easy and reliable

TOMORROW'S PRINTING TODAY



Full range of interface options incl. Bluetooth® (Apple™ and Android™ compatible).

**Specifications** 

### CT-S801II

### POS, Receipt printer (thermal 3 inch /80mm)

#### **Features & Benefits**

- Paper exit: Top exit ideal for all retail applications
- Paper load: Easy paper loading
- Printing Speed: Ultra fast print out of receipts - up to 300mm per seconds
- Display: LCD display for easy configuration and operation
- Low space requirement integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking

es



High speed printing with unique ease of use

Model	CT-S801II
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	300 mm/sec.
Print Width (maximum)	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
Media Width (min to max)	58 / 60 / 80 / 82.5 mm
Media Thickness (min to max)	65 to 75 μm or 75 to 85 μm
Main Interface	None: interface card slot for optional card
Interface	Ethernet + USB host, Premium Wireless LAN, Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB, USB with hub, Powered USB
Power supply	110 - 240 V, 50/60 Hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS <sup>TM</sup>
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
Cutter	Guillotine type, full and partial
Warranty	2 years including head and cutter
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A, VCCI

## CT-S801II

POS, Receipt printer (thermal 3 inch / 80mm)

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

## CT-S801II

POS, Receipt printer (thermal 3 inch / 80mm)