

SD1000J - 10"



- High resolution 10" LCD display
- Multiple Interface: USB-C alt mode or VGA, HDMI for option
- Support pole type or desktop stand or VESA 75 x 75mm mounting
- USB interface provides a single-cable solution combines power, video signal
- White or Black color available

SD1000J - 10”

Model	SD1000J-VH	SD1000J-C
Display Size	10 inch (4:3)	
Interface	VGA+HDMI	USB-C
Resolution	1024 x 768	
Power Source	DC 12V adaptor (1500mA)	USB-C: Power by USB-C
Power Consumption	12V / 400mA	USB-C: 5V / 1A HDMI: DC 12V / 400mA
Active Area	196.6 (H) x 147.4 (V) mm	
Display Type	TFT-LCD (Wide Viewing Angle)	
Back Light	LED	
White Luminance	310 cd/m²	
Contrast Ratio	900	
Response Time Tr+Tf	20 msec	
Viewing Angle	178° (Horizontal) / 178° (Vertical)	
Operating Temperature	0°C ~ 40°C	
Touch (Option)	Touch Function	Projective Capacitive Multi Touch
	Input Method	Finger
	Interface	USB
	Glass Type	Toughened Glass
	Optical Characteristics	Transparency > 85%
Physical Dimension	242.7(L) x 187.2(W) x 30(D) mm	
VESA Mount	VESA 75 x 75 mm	
EMC / Safety Standards	CE, FCC, Lot5	CE, FCC