

SD1200 – 12.1"



-
- Sleek & slim bezel 4:3 12.1" display
 - Multiple Interface: USB-C alt mode or VGA+HDMI for option
 - Support desktop stand or VESA 75 x 75mm mounting
 - Optional projective capacitive multi-touch screen
 - White or Black color available

SD1200 – 12.1”

Model	SD1200	SD1200-C
Display Size	12.1 inch (4:3)	
Interface	VGA+HDMI	USB-C
Resolution	1024 x 768	
Power Source	DC 12V adaptor (1500mA)	USB-C: Power by USB-C
Power Consumption	12V / 1.35A	USB-C: 18W HDMI: DC 12V / 1.35A
Active Area	245.76 (H) x 184.32 (V) mm	
Display Type	TFT-LCD (Wide Viewing Angle)	
Back Light	LED	
White Luminance	500 cd/m²	
Contrast Ratio	1000	
Response Time Tr+Tf	35 msec	
Viewing Angle	178° (Horizontal) / 178° (Vertical)	
Operating Temperature	0°C ~ 40°C	
Touch (Option)	Touch Function	Projective Capacitive Multi Touch
	Input Method	Finger
	Interface	USB
	Glass Type	Toughened Glass
	Optical Characteristics	Transparency > 86%
Physical Dimension	275.8(L) x 216.8(W) x 37.7(D) mm	
VESA Mount	VESA 75 x 75 mm	
EMC / Safety Standards	CE, FCC	