

SD-1160J

11.6" LCD DISPLAY

WIDE VIEWING ANGLE DISPLAY



FULL HD Widescreen LCD Monitor
At 1920 × 1080 Resolution

OVERVIEW

Interface: USB, VGA, HDMI, USB-C alt mode, different interface option
Projective capacitive touch as option
Pole type or solid stand or VESA 75*75 mm mounting
White or black chassis
Rear I/O ports for easy access



Capacitive Touch Panel



Slim Design with Wide Physical View Angle


SD-1160J 11.6" LCD MONITOR

SPECIFICATION

		SD1160J-USB	SD1160J- VGA-HDMI	SD1160J-C	SD1160J-R
Display Size		11.6 inch (16:9)			
Interface		USB	VGA + HDMI (DP optional)	USB-C(ALT Mode) + HDMI	HDMI
Resolution		1920x1080			1366x768
Power Source		5V USB 3.0 X 2 or 5V USB + DC 5V Adapter or 5V USB + DC 12V Adapter	DC 12V Adapter (1500mA)	USB-C : Power by USB-C HDMI : DC 12V Adapter (1500mA)	DC 12V Adapter (1500mA)
Power Consumption		5V/1.7A or 5V/1.7A or 12V/0.64A	12V / 300mA	USB-C : 8W HDMI : DC 12V / 300mA	12V / 350mA
Active Area		256.32(H) x 144.18(V)mm			
Display Type		TFT-LCD (Wide viewing angle)			
Back Light		LED			
White Luminance		375 cd/m ²			220 cd/m ²
Contrast Ratio		1000			
Response Time Tr+Tf		25 msec			30 msec
Viewing Angle		178° (Horizontal)/178° (Vertical)			
Operating Temperature		0° C~40° C (Operating)			
Touch (Option)	Touch Function	Projective Capacitive Multi Touch			
	Input Method	Finger			
	Interface	USB			
	Glass Type	Toughened Glass			
	Optical Characteristics	Transparency > 85%			
Physical Dimension		298(L) x 186(W) x 37(D)mm			
VESA Mount		VESA 75 mm			
EMC / Safty Standards		FCC, CE	FCC, CE, VCCI	FCC, CE	FCC, CE

I/O TYPES

USB



VGA and HDMI (USB-B for touch)



USB-C alt mode

