

SD-1330J

13.3" LCD DISPLAY

Support DP Alt Mode
THE MOST ADVANCED
POS DISPLAY

True Flat Design
1920 x 1080 FULL HD



OVERVIEW

Single USB Type-C to Type-C cable provides power, signal, and touch

Projective capacitive touch as option

Solid stand or VESA 75*75 mm mounting

White or black chassis

Rear I/O for easy access



Capacitive Touch Panel



Wide Physical View Angle


SD-1330J USB TYPE-C LCD DISPLAY

SPECIFICATION


		SD1330J-USB	SD1330J-VGA-HDMI	SD1330J-C
Display Size		13.3 inch (16 : 9)		
Interface		USB	VGA + HDMI (DP optional)	USB-C(ALT Mode) + HDMI
Resolution		1920x1080		
Power Source		5V USB + USB	DC 12V Adapter (1500mA)	USB-C : Power by USB-C HDMI : DC 12V Adapter (1500mA)
Power Consumption		5V/1.2A	12V / 200mA	USB-C : 6.5 W HDMI : DC 12V / 200mA
Active Area		293.76 (H) x 165.24 (V)mm		
Display Type		TFT-LCD (Wide viewing angle)		
Back Light		LED		
White Luminance		250 cd/m ²		
Contrast Ratio		1000		
Response Time Tr+Tf		30 msec		
Viewing Angle		170° (Horizontal)/170° (Vertical)		
Operating Temperature		0° C~40° C (Operating)		
Touch (Option)	Touch Function	Projective Capacitive Multi Touch		
	Input Method	Finger		
	Interface	USB		
	Glass Type	Toughened Glass		
	Optical Characteristics	Transparency > 86%		
Physical Dimension		330.8(W) x 213(L) x 28.5(D) mm		
VESA Mount		VESA 75 mm		
EMC / Safty Standards		FCC, CE	FCC, CE	FCC, CE

I/O TYPES

USB



VGA and HDMI (USB-B for touch)



USB-C alt mode

