

SD-1560

15.6" TOUCH SCREEN
MONITOR

Wide Screen 16:9
Multiple Interface with
Ultra Slim and Professional

True Flat Design
1920x1080 FULL HD



OVERVIEW

Interface: USB-C (Alt Mode), USB, or HDMI
Capacitive touch as option.
Ultra slim and compact design



SD-1560 TOUCH SCREEN MONITOR

SPECIFICATION


	SD1560	SD1560C
Display Size	15.6 inch (16:9)	
Interface	HDMI	USB-C(ALT Mode) + HDMI
Resolution	1920x1080	
Power Source	DC 12V Adapter 1.5A	USB-C : Power by USB-C HDMI : DC 12V Adapter (1500mA)
Power Consumption	12V / 450mA	USB-C : 7.5 W HDMI : DC 12V / 450mA
Active Area	344.16(H) × 193.59(V)mm	
Display Type	TFT-LCD (Wide viewing angle)	
Back Light	LED	
White Luminance	280 cd/m2	
Contrast Ratio	800	
Response Time Tr+Tf	30 msec	
Viewing Angle	170° (Horizontal)/170° (Vertical)	
Operating Temperature	0° C~40° C (Operating)	
Touch (Option)	Touch Function	Projective Capacitive Multi Touch
	Input Method	Finger
	Interface	USB
	Glass Type	Toughened Glass
	Optical Characteristics	Transparency > 86%
Physical Dimension	377.9(W) x 244.3(L) x 28(D) mm	
VESA Mount	VESA 75 mm	
EMC / Safty Standards	FCC, CE, VCCI (HDMI only)	FCC, CE

I/O TYPES

A. HDMI + DC + USB B_type Interface



B. USB-C + HDMI Interface



USB-C with M2 threaded HDMI DC 12V Power