

FLYTECH

PRIMELCO 
SYSTEM DEVICE


AIO-458

18.5" Widescreen POS Solution



Unleash Power and Versatility

AIO-458 features the latest [Intel® Alder Lake-N](#) platform, delivering superior performance and efficiency. With seamless compatibility across Windows, Linux, and Android 13, it ensures flexibility and reliability for all your operational needs.





Larger Screen for Easy Operation

With an 18.5" wide touchscreen (16:9 ratio), it offers a more intuitive user experience and high-quality images that fully realize the visual effects you require.

Maximize Operational Efficiency

AIO-458 offers a wide range of peripherals that can be easily mounted on the left/right sides of the display. Enjoy seamless integration and enhanced functionality, creating a personalized solution that empowers your business and elevates the customer experience.

NFC



Scanner



Fingerprint



MSR



Simpler Maintenance

Effortlessly access the RAM and SSD by simply removing the back cover, ensuring easy field serviceability. This design minimizes downtime and allows for quick upgrades, making it easier to maintain optimal performance.



Streamline
Maintenance
Process




Minimize
Downtime



Smooth
Operations






Unlock More Possibilities

Experience flexible transformation between desktop POS, wall-mounted KDS (Kitchen Display System), and self-service kiosks in both retail and hospitality environments.

I/O Ports



Specifications

| | | |
|---------------------|-------------------------|---|
| System | Motherboard | G35 |
| | Processor | Intel® Alder Lake N: N97, i3-N305 |
| | Memory | 8GB DDR4 (up to 16GB) |
| | Storage | 128GB SSD M.2 (up to 256GB) |
| Expansion | M.2 (E Key) | 1 |
| Display | Size and Resolution | 18.5" 1366x768 |
| | Touch Screen | True-Flat PCAP multi-touch |
| I/O Ports | USB Type-A | 2x USB3.0 4x USB2.0 |
| | USB Type-C | 1x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A) |
| | FeDP | 1x Flytech proprietary miniDP |
| | Serial Port | 3x RJ48 (standard RS232) (default 0V; 5V,12V) |
| | LAN | 1x RJ45 |
| | Cash Drawer | 1x RJ11 |
| | DC Jack | 1x 4PIN (with latch) |
| | | 2x Powered USB 12V 1x Powered USB 24V |
| Optional I/O Ports | Powered USB | 1x 3W (Option) |
| Audio | Internal Speaker | |
| Indicator | Power Button | 1 |
| Power | Power Adapter | 65W/19V (120W/19V with 2x PUSB 12V & 1x PUSB 24V) |
| Communication | WLAN + BT | 802.11 series + BT5.2 (Option) |
| Peripheral (option) | MSR | 3-Track MSR (USB) |
| | Fingerprint | Fingerprint Reader (USB) |
| | NFC | NFC Reader (USB) (<i>*project-based</i>) |
| | 2D Scanner | 2D Scanner (USB) (<i>*project-based</i>) |
| | Customer Display | LCM display 2 x 20 characters (USB) |
| | 2 nd Display | 11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch) |
| Certificate | EMC & Safety | FCC Class A, CE Mark, LVD |
| Environment | Operating Temperature | 0°C ~ 35°C (32°F ~ 95°F) |
| | Storage Temperature | -20°C ~ 60°C (-4°F ~ 140°F) |
| | Humidity | 20% ~ 85% RH non-condensing |
| Dimensions | W x H x D | 460 x 277 x 203 mm (18.1" x 10.9" x 8") |
| Mounting | VESA Mount | 100 x 100 |
| OS Supported | | Windows 10 IoT Enterprise, Linux, Android 13.0 |

※ Product specifications and data are subject to change without notice.

FLYTECH

PRIMELCO 
SYSTEM DEVICE



AIO-458

18.5" Widescreen POS Solution

