



PA760 Omni-Channel PDA

Enterprise level, rugged exterior, powerful interior

Accessories



Optional Gun grip:
Standard IP54 / UHF IP54
or Extra LR 2D imager IP54



**4-slot charging/
ethernet cradle**




**Charging/
Ethernet Cradle**




**Extended 6000
mAh battery**




5.5" Vivid
Colour LCD




Android 9.0
GMS




CPU
X8 Core




Limitless
POGO
scalability



RAM
4 GB RAM



4000 mAh
mono-battery



1D/2D
Imager



Dependable - The PA760 is designed and developed to help you go further and above the competition!

Offering the latest OS of Android 9, a robust processor, and a rugged scanner, the PA760 also comes with the Google GMS license, makes your toughest work days easier. It is ideal for a variety of applications including inventory control in warehouse, inbound and outbound management in the retail industry, parking management and facilities inspection in field service, and flight ticket checking and mobile POS system in transportations.





PA760

v1.4 Specifications



Wide-angle and high bright LCD

The 5.5" high brightness sunlight readable LCD display (18:9) with High Resolution makes the PA760 extremely well readable in any environment - 500 nits display with direct bonding



Extreme durability

Easy hot-swap battery design without downtime. The 4200 mAh capacity mono battery (cover and battery as one) for quick swap to keep stay as efficient as possible. Lose little time charging because the PA760 is fully charged within 3 hours thanks to QC3.0.



Industrial strength exterior

The Unitech PA760 is fitted with a drop resistant (1.5m) and IP67 rated body to withstand the most rugged environments out there.



Scalability and Extensibility

Thanks to POGO pins on rear- and bottom side, the PA760 has limitless scalability options for future accessories such as gun grips and docking stations.

Software Support



SOTI TeamViewer airwatch

Buttons

Side SCAN button x 2 (Left / Right), Power button, User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button. Three touch key on touch panel(back/home/recent)

Data capture

Scanning Honeywell N6603 engine.
1D : UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Matrix 2 of 5, MSI, Trioptic,
2D: PDF417, MicroPDF417, GS1 Composite , Code11, Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code,
DOT Code, Digimarc, DPM
Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code
OCR : OCR-A, OCR-B, E13B (MICR)

RFID/NFC Frequency 13.56Mhz (NXP PN553)
ISO 14443 type A and B; FeliCa/Mifare and ISO 15693 standard

Power Source

Main battery Hot-swap battery standard 4000mAh / battery with cover in one piece / extended 6000mAh / battery with cover in one piece (optional)
Backup battery Warm swap battery - Keeps applications active up to 3 minute
Operation Typical operation Time >10 hours
Charging time <3 hours (supports QC4.0 quick charge)

Audio

Speaker 1 W output ,95 dB at 10cm, Microphone*22, noise cancellation, PPT headset support, cellular circuit switch voice

Enclosure

Weight 300g (with standard battery)
Dimension 163 mm x 75 mm x 17.4 mm

Environmental

Operating temperature -20°C to 50°C
Storage temperature -30°C to 60°C
Relative Humidity 5% ~ 95% (Non-Condensing)
Drop test to Concrete 1.5 meter without bumper
1.8 meter with bumper
Environmental Sealing IP67
ESD 8K / 15KV
Tumble 0.5m tumbles for 300 cycles and 600 drops

Accessories

Hand Strap 4-Slot Ethernet cradle (USB host)
Adapter (US, EU, UK plugs) 4-Slot Terminal Charging cradle
USB type C cable 4-Slot battery charger
Tray Ejector tool 12-Slot Terminal Charging cradle
Bumper (by model selection) Vehicle cradle
9H glass screen protector Mount-kits for Vehicle cadle
1-slot Terminal charging cradle
1-slot Terminal Ethernet cradle
Gun Grip for trigger only (IP54)
Gun Grip for extra Long range 2D Barcode reader (IP54)
Gun Grip for UHF reading (IP54)

Regulatory Approvals

CE, FCC, NCC, IC, VCCI, TELEC, CCC, SRRC, RoHS, CEC, BOB, GMS, N-Mark.

Operation System

CPU Qualcomm 660 Octa-core 2.2 GHz Processor
Memory RAM: 4GB, ROM: 64GB
OS Android 9.0 with GMS (Global and EU compatible through R)
AER Android Enterprise Recommended
SIM Nano-SIM X 2
Card Slot Micro SD/SDHC/SDXC (up to 128GB) + Dual Nano-SIM
Language Support Multiple Languages supported

Display

Gorilla Glass 3 with 5-point Capacitive Touch Panel 5.45" (18:9)
Color LCD 1440x720 High Resolution Display 500 cd/m2 Brightness

Camera/Photos/Video

Front: 5MP camera / Rear: 16MP camera / PDAF (Phase Detection Auto Focus) / LED flash light

Indicator

LED, speaker and vibration

Communication

Bluetooth® Bluetooth® 5 supported
Interface USB 2.0 Type-C USB (Host / Client) with I/O pogo pin expansion
USB USB OTG Type C Connector for PC/USB drive
POGO PIN connector for Cradle
WLAN IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/v, IPv4, IPv6
Security of WLAN: WEP, WPA/WPA2 PSK, 802.1x EAP, OWE, SAE
MIMO MIMO(2x2)
FAST ROAMING PMKID caching, 802.11r, OKC
WWAN Support VoLTE, LTE Advanced Support
Up to 400 Mbps CAT4 LTE downlink/uplink
LTE (FDD) – B1/B2/B3/B4/B5/B7/B8/B17/B20/B28
LTE (TDD) – B38/B39/B41
UMTS/HSPA+ (3G) – B1/B2/B5/B8
GSM/GPRS/EDGE Quad-Band (850/900/1800/1900MHz)
GPS *Support Dual Nano SIM Slot
Others GPS/GLONASS/Gallileo/Beidou and A-GPS
Support NFC, fingerprint
Sensor Acceleration, Motion, Light, E-compass, G-sensor, Light & Proximity Sensor
Vibration Ref. to MIL-STD 810G, Method 514.6, Procedure I, 0,04G2/Hz Random (20Hz to 2kHz); 60 minutes duration per axis, 3 axis

Unitech Europe

Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com

Specifications subject to change without notice. Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

unitech
because we care